



# ALDERLY RANGE




powered by  
**TRIDONIC**

60 degree



90 degree



IP IP20 IK02  L70/B50  
50,000 hrs

The Alderley LED downlighter is equipped with the state-of-the-art LED technology, making it an ideal choice for a wide range of commercial applications, boasting an efficacy of up to 111 lumens per watt.

The downlighter is available in three sizes and two colour temperatures, and comes with the option of a 60-degree or 90-degree reflector, making it suitable for various applications such as corridors and open plan areas.

The Alderly range seamlessly integrates with Trojan's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Diameter mm	Height mm	Cut out mm	CCT K	Weight kg
TLALD/1/1000/3K	10	1060	120	64	100	3000	0.5
TLALD/1/1000/4K	10	1110	120	64	100	4000	0.5
TLALD/2/1000/3K	10	1100	170	93	145	3000	0.8
TLALD/2/1000/4K	10	1120	170	93	145	4000	0.8
TLALD/2/2000/3K	20	2130	170	93	145	3000	0.8
TLALD/2/2000/4K	20	2210	170	93	145	4000	0.8
TLALD/3/2000/3K	20	2200	225	113	210	3000	1.2
TLALD/3/2000/4K	20	2250	225	113	210	4000	1.2
TLALD/3/3000/3K	30	3070	225	113	210	3000	1.2
TLALD/3/3000/4K	30	3180	225	113	210	4000	1.2

DD = DALI Dimmable  
E = Emergency  
60 = 60deg reflector

SD = SwitchDim  
ST = Self Test Emergency  
90 = 90deg reflector

MD = Mymesh Dim  
ME = Mymesh Emergency  
TW = Tunable White

CD = Casambi Dim  
SL\*\* = Slave