



EVESHAM RANGE



powered by
TRIDONIC




IP65

IK10

L80/B10
 72,000 hrs

The Evesham range incorporates impact resistant polycarbonate base and diffuser along with Tridonic high-performance LED board and driver making the bulkhead a highly efficient lighting fixture that can meet even the most rigorous energy-saving requirements. It is ideal for commercial and domestic use and has been designed to be both economical and efficient.

Supplied as CRI 80 as standard, with a high colour stability of 3 MacAdam steps, the Evesham is available with white or black base and either cool or warm white colour temperature and along with a range of control options including corridor function. The emergency range of the Evesham emergency versions are fitted with the latest lithium iron phosphate LiFePO4 battery technology, which has a 3-year battery warranty.

The Evesham range seamlessly integrates with Trojan's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Diameter mm	Height mm	Efficacy lm/W	CRI	CCT K
TLEVE/1500/3K	13	1519	318	92	114	80	3,000
TLEVE/1500/4K	13	1599	318	92	120	80	4,000
TLEVE/2000/3K	17	1995	318	92	114	80	3,000
TLEVE/2000/4K	17	2100	318	92	120	80	4,000
TLEVE/2500/3K	21	2447	318	92	114	80	3,000
TLEVE/2500/4K	21	2574	318	92	120	80	4,000

DD = DALI Dimmable SD = SwitchDim MD = Mymesh Dim CD = Casambi Dim
 E = Emergency ST = Self Test Emergency ME = Mymesh Emergency SL** = Slave
 CF = Corridor Function MW = Sensor On/Off WH = White base BL = Black base