



ASHURST RANGE



powered by
TRIDONIC



 **IP54**
 **IK02**
 **L80/B10**
50,000 hrs

The Ashurst downlighter is a premium-grade IP54 lighting fixture specifically designed for use in corridors, general purpose areas, toilets, showers, and healthcare applications. It is equipped with a sand blasted aluminium reflector that offers a good optical performance, enabling its suitability for a diverse range of lighting requirements.

The downlighter range is available in 3000K, 4000K and tunable white colour temperatures, providing flexibility in achieving the desired lighting ambience. The satin-etched reflector produces a pleasing appearance and the use of optimised thermal management technology results in an expected lifespan of 60,000 hours (L70) with a colour stability within 3 MacAdam steps.

The Ashurst range seamlessly integrates with Trojan's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Diameter mm	Height mm	Cut out mm	Efficacy lm/W	Weight kg
TLASH/1000/4K	9	1106	195	115	176	128	1.8
TLASH/1500/4K	12	1558	195	115	176	126	1.8
TLASH/2000/4K	17	2086	195	115	176	128	1.8
TLASH/2500/4K	20	2575	195	115	176	126	1.8
TLASH/3000/4K	24	3000	195	115	176	123	1.8
TLASH/3500/4K	28	3389	195	115	176	119	1.8
TLASH/4000/4K	26	4009	195	115	176	156	1.8
TLASH/4500/4K	33	4770	195	115	176	142	1.8
TLASH/5500/4K	40	5735	195	115	176	143	1.8

DD = DALI Dimmable
 E = Emergency
 3K = 3000K CCT

SD = SwitchDim
 ST = Self Test Emergency
 TW = Tunable White

MD = Mymesh Dim
 ME = Mymesh Emergency

CD = Casambi Dim
 SL** = Slave