



EVERSLEY RANGE



 IP65
  IK10
  L80/B10
72,000 hrs

The Eversley range incorporates impact resistant aluminium cast base and polycarbonate diffuser along with Tridonic high-performance LED board and driver making the bulkhead a highly efficient lighting fixture that can meet even the most rigorous energy-saving requirements. It is ideal for commercial and domestic use and has been designed to be both economical and efficient.

Supplied as CRI 80 as standard, with a high colour stability of 3 MacAdam steps, the Eversley is available with white or black base and either cool or warm white colour temperature and along with a range of control options including corridor function. The emergency range of the Eversley emergency versions are fitted with the latest lithium iron phosphate LiFePO₄ battery technology, which has a 3-year battery warranty.

The Eversley range seamlessly integrates with Trojan's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Length/Width mm	Height mm	Efficacy lm/W	CRI	CCT K
TLEVER/1500/3K	13	1519	276	97	114	80	3,000
TLEVER/1500/4K	13	1599	276	97	120	80	4,000
TLEVER/2000/3K	17	1995	276	97	114	80	3,000
TLEVER/2000/4K	17	2100	276	97	120	80	4,000
TLEVER/2500/3K	21	2447	276	97	114	80	3,000
TLEVER/2500/4K	21	2574	276	97	120	80	4,000

DD = DALI Dimmable SD = SwitchDim MD = Mymesh Dim CD = Casambi Dim
 E = Emergency ST = Self Test Emergency ME = Mymesh Emergency SL** = Slave
 CF = Corridor Function MW = Sensor On/Off WH = White base BL = Black base