



IP54



IK07



L90/B10
50,000 hrs

powered by
TRIDONIC

The Essington bed head range offers bi-directional illumination in four sizes. Produced from 1mm Zintec steel and fitted with a low glare opal diffuser giving a unique look whilst still having an IP54 rating, maintaining the environment required in a hospital. Twin circuit wiring is available for dual control of the direct and in-direct light.

The Essington range seamlessly integrates with Trojan's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Efficacy lm/W	Length mm	Width mm	Height mm
TLESS/300/2100/4K	14	2123	152	300	200	98
TLESS/300/2400/4K	17	2445	144	300	200	98
TLESS/300/2700/4K	19	2749	145	300	200	98
TLESS/600/4200/4K	29	4246	146	600	200	98
TLESS/600/4900/4K	34	4889	143	600	200	98
TLESS/600/5500/4K	39	5498	141	600	200	98
TLESS/900/6400/4K	43	6368	149	900	200	98
TLESS/900/7300/4K	50	7343	147	900	200	98
TLESS/900/8200/4K	57	8247	144	900	200	98
TLESS/1200/8500/4K	57	8491	149	1200	200	98
TLESS/1200/9200/4K	61	9152	150	1200	200	98
TLESS/1200/9800/4K	66	9778	148	1200	200	98

DD = DALI Dimmable

SD = SwitchDim

MD = Mymesh Dim

CD = Casambi Dim

E = Emergency

ST = Self Test Emergency

ME = Mymesh Emergency

SL** = Slave

TC = Twin Circuit (up & down)