





RG1	MACADAM 3/4	UGR <19	CR>80	L80B50 > 72.000	IP66 IK10	CE	2014/34/EU Ex db IIB+H2 T6 Gb Ex tb IIIC T85°Db
-----	----------------	------------	-------	-----------------------	--------------	----	---



Ref.	Size (mm)	Power (W)	Gross output (Lm)	T ^a colour (°K)	L (mm)	D (mm)	D + clamp (mm)	Packaging
PY113	600	12	2.281	4.000	748	150	208	1
PY123	600	24	4.561	4.000	748	150	208	1
PY213	1.200	24	4.561	4.000	1.357	150	208	1
PY223	1.200	48	9122	4.000	1.357	150	208	1
PY313	1.500	30	5.701	4.000	1.659	150	208	1
PY323	1.500	60	11.403	4.000	1.659	150	208	1

OPAL VERSION



Ref.	Size (mm)	Power (W)	Gross output (Lm)	Nettoutput (Lm)	T ^a colour (°K)	L (mm)	D (mm)	D + clamp (mm)	Packaging
PY1130	600	12	2.281	1756	4.000	748	150	208	1
PY1230	600	24	4.561	3512	4.000	748	150	208	1
PY2130	1.200	24	4.561	3512	4.000	1.357	150	208	1
PY2230	1.200	48	9122	7024	4.000	1.357	150	208	1
PY3130	1.500	30	5.701	4390	4.000	1.659	150	208	1
PY3230	1.500	60	11.403	8780	4.000	1.659	150	208	1