



IP IP20
  IK08
  L80/B50
 100,000 hrs

The Finlay suspended low-bay LED luminaire consists of a powder coated (RAL 7043) aluminium housing, a polycarbonate prismatic reflector and supplied with a hook and wire suspension kit.

The Finlay is available in 4000K, CRI 80 as standard and can be supplied as 3000K on request, with a high colour stability of 4 MacAdam steps.

The Finlay range seamlessly integrates with Trojan's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Diameter mm	Height mm	Efficacy lm/W	CRI	CCT K
TLFIN/4200/4K	27	4200	410	289	156	80	4000
TLFIN/6000/4K	39	6000	410	289	154	80	4000
TLFIN/8400/4K	55	8400	410	289	153	80	4000
TLFIN/10800/4K	71	10800	410	289	152	80	4000
TLFIN/12600/4K	82	12600	410	289	154	80	4000

DD = DALI Dimmable
E = Emergency

SD = SwitchDim
ST = Self Test Emergency

MD = Mymesh Dim
ME = Mymesh Emergency

CD = Casambi Dim
SL** = Slave