




TONTINE RANGE



powered by
TRIDONIC



IP IP65  **IK10**  **L90/B10**
72,000 hrs

The Tontine IP65 rated wall pack luminaire is ideal to provide general illumination at a mounting height of 3-6 metres. The electronic control gear can be accessed via the hinged polycarbonate diffuser.

The luminaire is available in various lumen outputs with a 4000K colour temperature as standard, 3000K colour temperature is available on request.

The Tontine range seamlessly integrates with Trojan's standard options, offering choices such as dimmable functionality and emergency configurations. Additionally, these luminaires can be seamlessly integrated into our intelligent lighting systems through wireless options, ushering in a new era of versatile illumination solutions.

Part code	Power W	Output lm	Height mm	Width mm	Depth mm	Efficacy lm/W	CCT K
TLTON/1500/3K	14	1436	308	288	182	102	3,000
TLTON/1500/4K	14	1512	308	288	182	106	4,000
TLTON/3000/3K	29	2824	308	288	182	98	3,000
TLTON/3000/4K	29	2973	308	288	182	102	4,000
TLTON/4000/3K	41	3766	308	288	182	92	3,000
TLTON/4000/4K	41	3964	308	288	182	97	4,000

DD = DALI Dimmable SD = SwitchDim MD = Mymesh Dim CD = Casambi Dim
 E = Emergency ST = Self Test Emergency ME = Mymesh Emergency SL** = Slave
 CF = Corridor Function MW = Sensor On/Off