




208002

FACE-UP MINI HP

Uplight for outdoor installation on a ground/floor surface. Phosphochromatised and polyester powder coated die-cast copper-free aluminium, tempered safety glass and stainless steel screws. Remote constant current max 700mA needed, with 3 CREE XP-G3 LED. IP67 rating.



350 mA - LED POWER 3W

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
high-power led	8°	300	100.00
high-power led	20°	287	95.80
high-power led	40°	278	92.80
3000°K warm-white			
high-power led	8°	306	102.00
high-power led	20°	293	97.80
high-power led	40°	284	94.80
4000°K neutral-white			
high-power led	8°	312	104.00
high-power led	20°	300	99.80
high-power led	40°	290	96.80

Finish color options:

Textured Grey
RAL 9006

Anthracite Grey
RAL 7016

Matt Black
(on request)

Technical features

IP67

IK08

CE

5
YEARS

III










NEW

Technical data










Wattage	MAX 6 WATT
IP Rating	IP67
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminium
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	3 x CREE XP-G3 LED
Screws	Stainless steel
Remote driver	Constant current max 700mA
Glass	Tempered
Power cable	1 mt. power cable included
Gross weight	1,20 Kg



500 mA - LED POWER 4.5W

light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white				
high-power led		8°	378	83.75
high-power led		20°	360	80.25
high-power led		40°	350	77.75
3000°K warm-white				
high-power led		8°	387	86.25
high-power led		20°	373	82.75
high-power led		40°	360	80.25
4000°K neutral-white				
high-power led		8°	396	87.88
high-power led		20°	380	84.50
high-power led		40°	369	82.00

700 mA - LED POWER 6W


light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white				
high-power led		8°	538	89.70
high-power led		20°	512	85.33
high-power led		40°	501	83.60
3000°K warm-white				
high-power led		8°	546	90.69
high-power led		20°	522	87.20
high-power led		40°	507	84.60
4000°K neutral-white				
high-power led		8°	558	93.00
high-power led		20°	534	89.00
high-power led		40°	518	86.30

remote driver selection

brand	manufacturer code	type	watt	IP rate	numbers of fixtures
ALVIT Italy	AL1435S-IP	constant current 350mA	14W	IP67	min 1 - max 4
ALVIT Italy	AL1450S-IP	constant current 500mA	14W	IP67	min 1 - max 3
ALVIT Italy	AL1470S-IP	constant current 700mA	14W	IP67	min 1 - max 2
TCI Italy	152014/350	constant current 350mA	17W	IP68	min 1 - max 5
TCI Italy	152014/500	constant current 500mA	24W	IP68	min 1 - max 5
TCI Italy	152014/700	constant current 700mA	30W	IP68	min 1 - max 4

OPTIONAL

AC120
HONEYCOMB
LOUVER



AC122
SPIKE

