




208003

## FACE-UP MEDIUM COB

Uplight for outdoor installation on a ground/floor surface. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium, tempered safety glass and stainless steel screws. With 1 direct 220-240V LUMENS "EDC 47C" COB LED. IP67 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
cob led	18°	1.000	66.67
cob led	36°	980	66.34
cob led	60°	960	64.00
<b>4000°K neutral-white</b>			
cob led	18°	1.050	70.00
cob led	36°	1.030	68.67
cob led	60°	1.000	66.67
<b>2700°K CCT</b> available on request			

### Finish color options:

- Textured Grey RAL 9006
  Anthracite Grey RAL 7016
  Matt Black (on request)


### Technical features



### Technical data

Wattage	15 WATT
IP Rating	IP67
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminium
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	1 x LUMENS "EDC 47C" COB LED
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built-in
Glass	Tempered
Power cable	1 mt. power cable included
Gross weight	2,00 Kg

AC121  
HONEYCOMB  
LOUVER



AC123  
SPIKE

