



505001

NANOSTEP ROUND XXS

Round shape wall-recessed luminaire for outdoor installation. Body and frontal cover in hard anodized aluminum with phospho-chromatised and polyester powder coating, tempered safety glass, moulded silicone gasket. Asymmetrical light distribution. Remote constant current 350mA driver needed, with 1 CREE XP-G2 LED. IP68 rating.

| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| 2700°K warm-white | | | |
| high-power led | 15° | 65 | 65.00 |
| high-power led | 30° | 55 | 55.00 |
| high-power led | 45° | 50 | 50.00 |
| 3000°K warm-white | | | |
| high-power led | 15° | 70 | 70.00 |
| high-power led | 30° | 60 | 60.00 |
| high-power led | 45° | 55 | 55.00 |
| 4000°K neutral-white | | | |
| high-power led | 15° | 80 | 80.00 |
| high-power led | 30° | 70 | 70.00 |
| high-power led | 45° | 65 | 65.00 |



Finish color options:

Textured Grey RAL 9006
 Anthracite Grey RAL 7016
 Matt Black (on request)

remote driver selection

| brand | manufacturer code | type | watt | IP rate | numbers of fixtures |
|-------------|-------------------|------------------------|-------|---------|---------------------|
| ALVIT Italy | AL1435S-IP | constant current 350mA | 14W | IP67 | min 1 - max 8 |
| Meanwell | LPC-20-350 | constant current 350mA | 16.8W | IP67 | min 4 - max 12 |

Technical features



Technical data

| | |
|---------------|------------------------------------------------------------|
| Wattage | 1 WATT |
| IP Rating | IP68 |
| IK Rating | IK08 |
| Material | Hard anodized aluminium body and trim |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | Nr. 1 CREE XP-G2 LED |
| Remote driver | Constant current 350 mA |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Cable gland | M12 |
| Power cable | 0.3 mt. neoprene power cable included |
| Gross weight | 0,50 Kg |

