










403107

NANOWALL ROUND XS 01

Wall applique for outdoor installation on a façade/wall, with one side light only. Body in anodized aluminum with phosphochromatised and polyester powder coating, tempered safety glass, moulded silicone gasket and stainless steel screws. Constant current max 700mA remote driver needed. With 1 x CREE "XP-L" LED. IP66 rating.



| 350 mA – LED POWER 1.2W | | | | |
|---------------------------------|---|-------------------|------------------------|--|
| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) | |
| 3000°K warm-white | | | | |
| high-power led |  10° | 138 | 115.00 | |
| high-power led |  30° | 132 | 110.00 | |
| high-power led |  45° | 125 | 104.00 | |
| 4000°K neutral-white | | | | |
| high-power led |  10° | 144 | 120.00 | |
| high-power led |  30° | 137 | 114.00 | |
| high-power led |  45° | 131 | 109.00 | |
| 2700°K CCT available on request | | | | |

Finish color options:

 Textured Grey RAL 9006
  Anthracite Grey RAL 7016
  Matt Black (on request)







Technical features









Technical data

| | |
|---------------|--|
| Wattage | MAX 2.5 WATT |
| IP Rating | IP66 |
| IK Rating | IK08 |
| Material | Hard anodized aluminum |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | 1 x CREE "XP-L" LED |
| Screws | Stainless steel |
| Remote driver | Constant current max 700mA |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Power cable | 0.3 mt. power cable included |
| Gross weight | 0,60 Kg |



| 500 mA - LED POWER 1.7W | | | | |
|--|---|--|-------------------|------------------------|
| light source | light beam options | | lumen output (lm) | lumin. efficacy (lm/w) |
| 3000°K warm-white | | | | |
| high-power led |  10° | | 196 | 115.00 |
| high-power led |  30° | | 187 | 110.00 |
| high-power led |  45° | | 177 | 104.00 |
| 4000°K neutral-white | | | | |
| high-power led |  10° | | 204 | 120.00 |
| high-power led |  30° | | 194 | 114.00 |
| high-power led |  45° | | 186 | 109.00 |
| 2700°K CCT available on request | | | | |

| 700 mA - LED POWER 2.5W | | | | |
|--|---|--|-------------------|------------------------|
| light source | light beam options | | lumen output (lm) | lumin. efficacy (lm/w) |
| 3000°K warm-white | | | | |
| high-power led |  10° | | 288 | 115.00 |
| high-power led |  30° | | 275 | 110.00 |
| high-power led |  45° | | 260 | 104.00 |
| 4000°K neutral-white | | | | |
| high-power led |  10° | | 300 | 120.00 |
| high-power led |  30° | | 285 | 114.00 |
| high-power led |  45° | | 273 | 109.00 |
| 2700°K CCT available on request | | | | |

| remote driver selection | | | | | |
|-------------------------|-------------------|------------------------|------|---------|---------------------|
| brand | manufacturer code | type | watt | IP rate | numbers of fixtures |
| ALVIT Italy | AL1435S-IP | Constant current 350mA | 14W | IP67 | min 1 - max 8 |
| ALVIT Italy | AL1450S-IP | Constant current 500mA | 14W | IP67 | min 1 - max 6 |
| ALVIT Italy | AL1470S-IP | Constant current 700mA | 14W | IP67 | min 1 - max 4 |

OPTIONAL

AC055
STANDARD GLARE
SHIELD XS



AC056
SUPER COMFORT
GLARE SHIELD XS



AC066
HONEYCOMB LOUVER

