








403111

NANOWALL SQUARE XS 01

Wall applique for outdoor installation on a façade/wall, with one side light only. Body in anodized aluminum with phospho-chromatised and polyester powder coating, tempered safety glass, moulded silicone gasket and stainless steel screws. Constant current max 700mA remote driver needed. With 1 x CREE "XP-L" LED. IP66 rating.



350 mA - LED POWER 1.2W

light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led		10°	138	115.00
high-power led		30°	132	110.00
high-power led		45°	125	104.00
4000°K neutral-white				
high-power led		10°	144	120.00
high-power led		30°	137	114.00
high-power led		45°	131	109.00
2700°K CCT available on request				

Finish color options:

 Textured Grey RAL 9006
  Anthracite Grey RAL 7016
  Matt Black (on request)







Technical features









Technical data

Wattage	MAX 2.5 WATT
IP Rating	IP66
IK Rating	IK08
Material	Hard anodized aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 x CREE "XP-L" LED
Screws	Stainless steel
Remote driver	Constant current max 700mA
Glass	Tempered
Power cable	0.3 mt. power cable included
Gross weight	0,65 Kg



500 mA - LED POWER 1.7W				
light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led	 10°		196	115.00
high-power led	 30°		187	110.00
high-power led	 45°		177	104.00
4000°K neutral-white				
high-power led	 10°		204	120.00
high-power led	 30°		194	114.00
high-power led	 45°		186	109.00
2700°K CCT available on request				

700 mA - LED POWER 2.5W				
light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led	 10°		288	115.00
high-power led	 30°		275	110.00
high-power led	 45°		260	104.00
4000°K neutral-white				
high-power led	 10°		300	120.00
high-power led	 30°		285	114.00
high-power led	 45°		273	109.00
2700°K CCT available on request				

remote driver selection					
brand	manufacturer code	type	watt	IP rate	numbers of fixtures
ALVIT Italy	AL1435S-IP	Constant current 350mA	14W	IP67	min 1 - max 8
ALVIT Italy	AL1450S-IP	Constant current 500mA	14W	IP67	min 1 - max 6
ALVIT Italy	AL1470S-IP	Constant current 700mA	14W	IP67	min 1 - max 4

OPTIONAL

AC055
STANDARD GLARE
SHIELD XS



AC056
SUPER COMFORT
GLARE SHIELD XS



AC066
HONEYCOMB LOUVER

