



403105

NANOWALL ROUND XXS 01


Wall applique for outdoor installation on a façade/wall, with one side light only. Body in anodized aluminum with phospho-chromatised and polyester powder coating, tempered safety glass, moulded silicone gasket and stainless steel screws. Constant current 350mA remote driver needed. With 1 x CREE "XP-G2" LED. IP66 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
high-power led	8°	70	70.00
high-power led	32°	60	60.00
high-power led	45°	55	55.00
3000°K warm-white			
high-power led	8°	75	75.00
high-power led	32°	65	65.00
high-power led	45°	60	60.00
4000°K neutral-white			
high-power led	8°	80	80.00
high-power led	32°	70	70.00
high-power led	45°	65	65.00

Finish color options:


- Textured Grey RAL 9006
- Anthracite Grey RAL 7016
- Matt Black (on request)

Technical features



Technical data

Wattage	1 WATT
IP Rating	IP66
IK Rating	IK08
Material	Hard anodized aluminum
Coating	polyester powder coating with phosphochromating pre-finish
Light Source	1 x CREE "XP-G2" LED
Screws	Stainless steel
Remote driver	Constant current 350mA
Glass	Tempered
Power cable	0.3 mt. power cable included
Gross weight	0,35 Kg



AC0124
HONEYCOMB
LOUVER

remote driver selection

brand	manufacturer code	type	watt	IP rate	numbers of fixtures
ALVIT Italy	AL1435S-IP	Constant current 350mA	14W	IP67	min 1 - max 8
Meanwell	LPC-20-350	Constant current 350mA	16.8W	IP67	min 4 - max 12