














601603-04

# PERISCOPE 02

500mm height “L-shape” bollard, for outdoor installation, one-side downward asymmetrical light distribution, phospho-chromatised and polyester powder coated extruded aluminum body. Tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with CREE “XP-G2” LED. IP65 rating.



601603		PERISCOPE 02 - 7 WATT - NR. 4 x CREE “XP-G2” LED	
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	 Asymmetric	805	115.00
<b>4000°K warm-white</b>			
high-power led	 Asymmetric	847	121.00
<b>Colors options</b>			
 Textured Grey RAL 9006  Anthracite Grey RAL 7016  Matt Black (on request)			

601604		PERISCOPE 02 - 14 WATT - NR.8 x CREE “XP-G2” LED	
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	 Asymmetric	1.610	115.00
<b>4000°K warm-white</b>			
high-power led	 Asymmetric	1.694	121.00
<b>Colors options</b>			
 Textured Grey RAL 9006  Anthracite Grey RAL 7016  Matt Black (on request)			

## Technical features



## Available on request



## Technical data

IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Screws	Stainless steel
Transformer	Electronic power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M16 rubber grommet
Power cable	0,5 mt. neoprene power cable included
Gross weight	4,50 Kg

