




502017

STEP LINEAR 06

Recessed linear steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered frosted glass diffuser, polypropilene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 15 low-power SMD5630 LED. IP65 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|---|-------------------|------------------------|
| 3000°K warm-white | | | |
| SMD5630 |  asymmetric 120° | 180 | 25.71 |

Finish color options:

 Textured Grey
RAL 9006

Technical features



Technical data

| | |
|--------------|---|
| Wattage | 7 WATT |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Material | High corrosion resistance die-cast copper-free aluminum body and frame. |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | NR. 15 x SMD5630 LED |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Cable | 0.5 mt. neoprene power cable included |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Gross weight | 1,00 Kg |

