




401017

TECH MEDIUM 01 ROUND PRO

Round wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-L LED. IP65 rating.



| light source* | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led | 10° | 1.300 | 92.86 |
| high-power led | 30° | 1.230 | 87.86 |
| high-power led | 45° | 1.170 | 83.57 |

* Other light colors available on request: Neutral-white

Finish color options:



Technical features



Technical data

| | |
|----------------|---|
| Wattage | 14 WATT |
| IP Rating | IP65 |
| IK Rating | IK09 |
| Material | High corrosion resistance die-cast copper-free aluminium body |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | NR. 5 CREE "XP-L" LED down |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Gasket | Silicone rubber |
| Rubber grommet | M20 Rutaseal® in EPDM |
| Glass | Tempered |
| Gross weight | 3,00 Kg |

