







401102

## WAVE 2.0


Surface mounted luminaire for outdoor installation on window sill, with asymmetric 8°x170° “window-washer” light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x CREE XHP35 LED. IP65 rating.



170°  
SINGLE INSTALLATION,  
IN THE MIDDLE.  
SUGGESTED FOR  
SMALL / MEDIUM  
SIZE WINDOWS



170°  
DOUBLE INSTALLATION,  
ON BOTH SIDES.  
SUGGESTED IN CASE  
OF HIGH LIGHTING  
PERFORMANCE  
NEEDED



170°  
DOUBLE  
INSTALLATION,  
IN THE MIDDLE.  
SUGGESTED FOR  
BIG SIZE WINDOWS



SIDE KNOCKOUT  
FOR CABLE

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
--------------	--------------------	-------------------	------------------------

### 3000°K warm-white

high-power led	8° x 170°	582	83.14
----------------	-----------	-----	-------

### 4000°K neutral-white

high-power led	8° x 170°	600	85.71
----------------	-----------	-----	-------

2700°K CCT available on request

### Finish color options:

 Textured Grey RAL 9006	 Anthracite Grey RAL 7016	 Matt Black (on request)
--	---	--

### Technical features



### Available on request



### Technical data

Wattage	7 WATT
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 1 x CREE “XHP35” LED
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	PMMA
Power cable	1 mt. power cable included
Gross weight	1,00 Kg

