Leo

Slim wall pack

TROJAN
INTELLIGENT LIGHTING SOLUTIONS

KEY FEATURES

- Input Voltage: 220-240Vac 50/60Hz
- IP Rating: IP65
- IK rating: IK10
- Efficiency: >100Lm/W
- CCT: 3000K / 4500K / 6500K
- CRI: >80
- Polycarbonate body and opal polycarbonate diffuser
- Ideal for coastal environments
- Multiple Cable Conduit Entries
- Complete with stainless steel anti-vandal screw
- Operating Temperature: -10°C ~ +35°C

DIMENSIONS



TECHNICAL INFORMATION

Part code	LED output (lm)	Luminaire power (W)	Luminaire efficacy (lm/W)	Colour temp (K)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
TLLEO/CCT	1800 / 2200 / 2600 / 3000	18 / 22 / 26 / 30	120	CCT selectable 3000/ 4500/ 6500	270	110	309	1.0

Options	Suffix
Switch dimmable	/SD
DALI dimmable	/DD

Microwave Sensor

Photocell

Accessories	
Plug and Play microwave sensor	TLLEO/MW
Plug and Play photocell	TLLEO/PC
Plug and Play emergency pack	TLLEO/EP

Emergency Pack